

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage	12V
Capacity (20-hour rate)	100Ah
Capacity (10-hour rate)	92Ah
Cold Cranking Amps (CCA, SAE J537)	925A
PHCA - 5-second pulse current	1750A
НСА	1325A
MCA	1150A
Reserve capacity	200 mins
Short circuit current (using IEC method)	2600A
Internal resistance at 20°C (using IEC method)	2.6 mΩ
Dimensions & Weight	

Length	330 mm
Width	173 mm
Height (to top of terminals)	239 mm
Height Container	218 mm
Weight	31.5 kg

Temperature

Operating Temperature Range	-40°C to +60°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 14/12/2021 14:17:49 Information correct at time of exporting PDF. Please check website for updates.



Solutions

EnerSys World Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627


EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug. Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780



Terminal Position

Terminal Type






Negative



ODP-AGM31A LEFT POSITIVE SAE TERMINALS

Positive





©2021 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates. Subject to revisions without prior notice. E.&O.E.