

# **ODX-AGM31A** (31-PC2150T)

# Technical Data Sheet

## **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

#### **Power & Performance**

Voltage	12V
Capacity (20-hour rate)	100Ah
Capacity (10-hour rate)	92Ah
Cold Cranking Amps (CCA, SAE J537)	1150A
PHCA - 5-second pulse current	2150A
HCA	1545A
MCA	1370A
Reserve capacity	205 mins
Short circuit current (using IEC method)	5000A
Internal resistance at 20°C (using IEC method)	$2.2\;\text{m}\Omega$

# **Dimensions & Weight**

Length	330 mm
Width	173 mm
Height (to top of terminals)	246 mm
Height Container	216 mm
Weight	35.3 kg

### **Temperature**

Operating Temperature Range	-40°C to +80°C
Optimum Storage Temperature	+20°C

#### **Accreditations**

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

# **Charging & self-discharge**

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

# Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).





# **Terminal Position**

# + -

# **Terminal Type**

#### **SAE Terminals**





PDF Generated at https://eu.odysseybattery.com 14/12/2021 13:54:55 Information correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780